

Product sheet

Salisbury

Product description	
Structure	Laminate flooring
Size	12 x 193 x 1215 mm
Surface	EIR Brushed
Texture	Hickory
Wear class	AC4
Bevel	Distressed bevel
Gloss	5 ± 3%
Core	High Density Fiberboard (HDF)
Wax on click	No
Underlay	No
Locking system	Drop loc - 2G Valinge liscenced lock system
Type of installation	Floated
Underfloorheating compatibility	Yes

Dimensional tolerance	
Standard	EN-13329
Thickness tolerance	± 0.5mm
Width tolerance	± 0.1mm
Length tolerance	± 0.5mm
Squareness	≤ 0.15mm
Height difference	≤ 0.10mm
Gap between planks	≤ 0.15mm
Cupping up	≤ 0.15 % over the width
Cupping down	≤ 0.20 % over the width
Bending up	≤ 0.5 % over the length
Bending down	≤ 1.0% over the length
Spring/Banana	≤ 0.3mm/m

CE marking	
Standard	EN-14041
Density, thickness	850 kg/m ³ , 12mm
Fire resistance	Cfl-S1
Formaldehyde emission	E1
PCP	≤ 1 ppm
Slipperiness	Class DS
Thermal conductivity	0.14 W / (mK)
Thermal Resistance	0.08 m ² .K/W

Physical features	
Standard	EN-13329
Level of use	Domestic heavy - class 23, Commercial general - class32
Core density	≥820 kg/m ³
MC tolerance	4 to 10 %
Thickness swelling	≤ 18%
Wear resistance	≥4000
Scratch resistance	≥ 4N
Surface soundness	≥ 1.00 N/mm ²
Static indentation	Pass
Impact resistance	IC2
Resistance to staining	Class 5
Light fastness	≥ 6 (Blue wool scale)

Others	
VOC-ISO 16000	A
Antibacterial surface (JIS Z2801)	Pass